

SPECIFICATION

[CHANNEL JOINT STRUCTURAL SYSTEM]

Cross Reference to Related Applications

This application is based on Provisional Application SN 60/406,778 filed August 29, 2002.

Background of Invention

[0001] A modular structural system which employs channel joints which are easy to assemble, light weight and capable of multiple configurations.

[0002] Typically prior systems weld all the joints to form a structure. As a result, the systems are difficult to ship and lack the flexibility to be adjusted to different spaces.

[0003] The prior art includes patent 4,063,422 to Morier which discloses a connector structure including a first connector structure for securement to the end of a post-like structure and a second connector element for securement to a further structure composite structural building panels and connection systems are shown in patent 6,314,704 to Bryant.

[0004] Other patents of general interest include patents 6,591,547; 6,405,507; and 5,536,457. None of the foregoing patents disclose a modular structural system similar to the present invention.

Summary of Invention

[0005] This invention relates to a modular channel joint structural system which offers rigidity and lightweight as well as ease of assembly. Instead of adding elements as squares and hardware to obtain a rigid joint, the present invention creates an interlocking system with matching extensions which slide into matching grooves or channels and are bolted together with only one bolt per joint. In a typical embodiment, aligned members with transverse grooves towards the ends thereof are joined together and to a third perpendicular member with inwardly curved extensions which engage the grooves. The third member includes a corresponding aperture on both sides thereof

which is positioned in line with an end notch in the aligned members. A bolt engages the apertures to hold the three members fixedly together.

[0006] Accordingly, an object of this invention is to provide a new and improved channel joint structural system.

[0007] Another object of this invention is to provide a new and improved lightweight module structural system.

[0008] A further object of this invention is to provide a new and improved channel joint structural system which includes members having channels engaged by downwardly extending end portions on another member to form a rigid joint.

[0009] A more specific object of this invention is to provide a new and improved modular joint structural system employing channel portions which are engaged by adjacent member portions and simply bolted together.

Brief Description of Drawings

[0010] The above and other objects of the invention may be more readily seen when viewing in conjunction with the accompanying drawings wherein.

[0011] FIG. 1 is an exploded perspective view of the channel joint structural system comprising the invention.

[0012] FIG. 2 is an end view of a modular component of the structure of FIG. 3; and.

[0013] FIG. 3 is a perspective view of a modular structure employing the novel joint of the invention.

Detailed Description

[0014] Referring not to FIG. 1 of the drawings, the invention comprises channel members 10 and 11 having mating ends 12 and 13 which each include a corresponding semicircular recess 14a, 14b and 15a, 15b in opposite portions 16a, 16b and 17a, 17b of a substantially rectangular faces 16a-d and 17a-d. Spaced a predetermined distance from the faces 16a, 16b and 17a, 17b are slots 18a, 18b and 19a, 19b which run parallel to the faces 16a, 16b and 17a, 17b.

[0015] A third member 20 includes a main body portion 21 of a substantially rectangular hollow configuration and opposite projecting end portions 22 and 23. The end portion 22 includes inwardly extending edges 24a-d which engages the slots 18a,

18b, 19a and 19b, respectively. Third member 20 also includes opposing threaded apertures 26 and 27 which are located in line with recesses 14a, 14b and 15a, 15b. When the slots 18a, 18b, 19a and 19b are engaged by the edges 24a-d the semicircular recesses 14a and 15a form circular aperture adjacent and in line with the aperture 26. Similarly, the recesses 14b and 19b form a circular aperture adjacent and in line with aperture 27. A threaded bolt 30 then engages the countersunk apertures 26 and 27 as well as the recesses 14a, 15a, and 14b, 15b to securely fasten the members 10, 11 and 20 together. While elongated straight members 10, 11 and 20 are shown in FIG. 1, the members may have other configurations apart from the joint portion described above.

[0016] FIG. 2 depicts an end view of a modular structure component 10 using the joint design proposed herein. The structure 40 includes members 41 and 42 which correspond at their ends 43a, 43b and 44a, 44b to the end portion 22 shown in FIG. 1. The members 46 and 47 are welded to the respective end portion. The final modular structure 50 is shown in FIG. 3 and comprises a plurality of end portions 40 joined by member 51 and 52.

[0017] While the invention has been explained by a detailed description of certain specific embodiments, it is understood that various modifications and substitutions can be made in any of them within the scope of the appended claims, which are intended also to include equivalents of such embodiments.